



ANSI516 Yellow

FALL ARRESTER HARNESSSES

Fall protection



Specific benefits



Comfort

- "H" configuration for greater comfort in women and men



Hygiene

- Can wash harnesses and textiles with neutral soap



Performance

- Certification above maximum rated load 100kg: product certified at 140kg



Ease of Use

- Ergonomic design facilitates user movement
- Automatic buckles optimize installation and safety of lock
- NFC system guarantees traceability

Applications

- Building
- Maintenance
- Chemical Industry
- Petrochemical
- Storage

Certifications and norms

ANSI Z359.11-2014



ANSI516 Yellow

FALL ARRESTER HARNESES

Fall protection

Standards - Details

Technical details

Composition of the main support	Kevlar®
Fastening	Buckles
Number of fall arrest attachment points	2
Number of total holding attachment points	2
Buckles	Automatic loop
Anti-fall point	Dorsal, Sternal
Holding point	Lateral
Color	Yellow
Size	One size
Benefits element	Fall indicator
Lifespan from manufacturing	10 years
Type of conditioning	box of 10
Sternal	1
Dorsal	1
Fall arrest work situations	Work positioning, Movement on lifeline, Restraint, Long vertical movement or movement on inclined surface, Long vertical movement or movement on inclined surface for rope access work, Short vertical movement or movement on inclined surface (less than 3 m), Long horizontal movement on vertical structure, Short horizontal movement (less than 3 m), Long movement with multi connection /disconnection



ANSI516

FALL ARRESTER HARNESSSES

Fall protection

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
ANSI516	Green-Red	M/L	ANSI516	7798408752845	0	5	1	11.45 kg	40.0 cm	30.0 cm	30.0 cm

 Multiple sales

 Minimum sales

 Box Width

 Box Depth

 Box Height