ANSI516 Green-Red

FALL ARRESTER HARNESSES

Fall protection



Certifications and norms

ANSI Z359.11-2014

Specific benefits



Comfort

 \cdot "H" configuration for greater comfort in women and men



Hygiene

· Can wash harnesses and textiles with neutral soap



Performance

· Certification above maximum rated load 100kg: product certified at 140kg



Ease of Use

- · Ergonomic design facilitates user movement
- · Automatic buckles optimize installation and safety of lock
- · NFC system guarantees traceability

Applications

- Building
- Maintenance
- Chemical Industry
- Petrochemical
- Storage







ANSI516 Green-Red

FALL ARRESTER HARNESSES

Fall protection

Standards - Details

Technical details

Composition of the main support	Kevlar [®]
Fastening	Buckles
Number of fall arrest attachment points	2
Number of total holding attachment points	2
Buckles	Automatic loop
Anti-fall point	Dorsal, Sternal
Holding point	Lateral
Color	Green-Red
Size	One size
Benefits element	Fall indicator
Lifespan from manufacturing	10 years
Type of conditioning	box of 10
Sternal	1
Dorsal	1
Fall arrest work situations	Work positioning, Movement on lifeline, Restraint, Long vertical movement or movement on inclined surface, Long vertical movement or movement on inclined surface for rope access work, Short vertical movement or movement on inclined surface (less than 3 m), Long horizontal movement on vertical structure, Short horizontal movement (less than 3 m), Long movement with multi connection /disconnection







ANSI516

FALL ARRESTER HARNESSES

Fall protection

Logistics information												
Reference	Colour	Size	Designation	EAN13	Box code		Å	Weight				
ANSI516	Green-Red	M/L	ANSI516	7798408752845	0	5	1	11.45 kg	40.0 cm	30.0 cm	30.0 cm	

Multiple sales

Minimum sales

Box Width

Box Depth

Box Height