



ANSI559 Rdeča

LONGES ABSORBEUR D'ÉNERGIE

Fall protection



Specific benefits



Comfort

- Elastic strap lanyard for easy movement and safety



Hygiene

- Harnesses and textiles can be washed with neutral soap



Performance

- Certification above the maximum rated load of 100 kg; product certified at 140 kg



Easy to use

- Automatic carabiners for secure and time-saving locking

Applications

- Stavba
- Vzdrževanje
- Kemična industrija
- Petrokemija
- Shranjevanje

Certifications and norms

Protects against risks



Heat



Fall



ANSI559 Rdeča

LONGES ABSORBEUR D'ÉNERGIE

Fall protection

Standards - Details

Technical details

Composition of the main support	Kevlar®, Steel
Max. length (m)	1,8 m
Length (m)	1,8
Gate opening (mm)	65
Opening (inch)	2.5545
With connector	yes
Color	Rdeča
Benefits element	Elastic strap
Lifespan from manufacturing (let)	10
Type of packaging	Box of 10
Fall arrest work situations	Vertical movement on a permanent structure, Movement on lifeline, Short vertical movement or movement on inclined surface (less than 3 m), Short horizontal movement (less than 3 m)
Lenght (ft)	5.9055








ANSI559

ENERGY ABSORBING LANYARDS

Fall protection

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
ANSI559	Red	1,8 m	ANSI559	0	0	10	1	16.2 kg	38.0 cm	25.0 cm	25.0 cm



Multiple sales



Minimum sales



Box Width



Box Depth



Box Height