



E26070 Siva

TUBULAR ROUND SLINGS

Fall protection



Specific benefits



Hygiene

· Harnesses and textiles can be washed with neutral soap

Applications

- Stavba
- Vzdrževanje
- Kemična industrija
- Petrokemija
- Prevoz
- Shranjevanje

Certifications and norms



E26070 Siva

TUBULAR ROUND SLINGS

Fall protection

Standards - Details

Technical details

Type of equipment	Round sling
Composition of the main support	Polyester
Max. length (m)	8 m
Strap width (mm)	75 mm
Min. length (m)	1 m
Color	Siva
Safe working load (kg)	4000 kg








E26070

TUBULAR ROUND SLINGS

Fall protection

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
WXE260700104	Grey	1 m	E26070	7798408753101	0	2	1	2.716 kg	40.0 cm	30.0 cm	30.0 cm
WXE260700204	Grey	2 m	E26070	7798408751961	0	2	1	4.404 kg	38.0 cm	25.0 cm	11.0 cm
WXE260700304	Grey	3 m	E26070	7798408752166	0	2	1	6.614 kg	38.0 cm	25.0 cm	17.0 cm
WXE260700404	Grey	4 m	E26070	7798408752517	0	4	1	17.404 kg	50.0 cm	40.0 cm	33.0 cm
WXE260700504	Grey	5 m	E26070	7798408755389	0	2	1	10.912 kg	40.0 cm	30.0 cm	30.0 cm
WXE260700604	Grey	6 m	E26070	7798408755396	0	2	1	12.662 kg	38.0 cm	25.0 cm	25.0 cm
WXE260700904	Grey	9 m	E26070	0	0	2	1	19.108 kg	40.0 cm	30.0 cm	30.0 cm

 Multiple sales

 Minimum sales

 Box Width

 Box Depth

 Box Height