



MEDBLOC AN13006C2

ANTICHUTE À RAPPEL AUTOMATIQUE

Fall protection



Specific benefits



Hygiene

· Harnesses and textiles can be washed with neutral soap



Easy to use

· NFC system guarantees traceability



Visibility

· Visual fall indicator for instant verification that the product is working properly

Applications

- Javna dela
- Second work / craftman
- Avtomobilska
- Nafta in plin (pridobivanje)
- Energija
- Shranjevanje

Certifications and norms



EN360

RFU 10.060
HORIZONTAL CERTIFICATION
RFU 11.062
128 KG

Protects against risks



Fall



MEDBLOC AN13006C2

ANTICHUTE À RAPPEL AUTOMATIQUE

Fall protection

Standards - Details

Technical details

Type of equipment	Webbing reel
Composition of the main support	ABS (Acrylonitrile Butadiene Styrene), Polyester
Strap width (mm)	25
ARA lenght (m)	6
ARA lenght (inch)	236.2206
Color	Črna
Connector (user side)	Small hook, steel, opening 21 mm
SIZE	6 m
Benefits element	Fall indicator
Lifespan from manufacturing (let)	10
Weight (kg)	1,6
Maximum load for one person (kg)	128
Fall arrest work situations	Vertical movement on a permanent structure, Long vertical movement or movement on inclined surface, Long horizontal movement on horizontal surface, Long horizontal movement on vertical structure








Fall protection

MEDBLOC AN13006C2

RETRACTABLE FALL ARRESTERS

Self-retractable webbing fall arrester for vertical and horizontal use, for distances of up to 6 metres

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
AN13006C2	Black	6 m	MEDBLOC AN13006C2	3295249264949	13295249264946	5	1	11.7 kg	23.0 cm	29.0 cm	50.4 cm



Multiple sales



Minimum sales



Box Width



Box Depth



Box Height