



WXETPRP100

TUBULAR ROUND SLINGS

Fall protection



Specific benefits



Hygiene

- Harnesses and textiles can be washed with neutral soap

Applications

- Nafta in plin (pridobivanje)

Certifications and norms



WXETPRP100

TUBULAR ROUND SLINGS

Fall protection

Standards - Details

Technical details

Type of equipment	Tubular round sling
Composition of the main support	Polyester
Max. length (m)	10 m
Strap width (mm)	100 mm
Min. length (m)	4 m
Color	Oranžna
SIZE	10 m
Type of packaging	Sold individually
Suitable for	High pressure
Pipe diameter- Maximum PSI	"2" - 20000 PSI, "3" - 20000 PSI, "4" - 10000 PSI








WXETPRP100

TUBULAR ROUND SLINGS

Fall protection

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
WXETPRP1000400	Orange	4 m	WXETPRP100	7798408755266	0	1	1	9.7 kg	38.0 cm	25.0 cm	25.0 cm
WXETPRP1000600	Orange	6 m	WXETPRP100	7798408755259	0	1	1	14.3 kg	38.0 cm	25.0 cm	25.0 cm
WXETPRP1000800	Orange	8 m	WXETPRP100	0	0	1	1	18.9 kg	38.0 cm	25.0 cm	25.0 cm
WXETPRP1001000	Orange	10 m	WXETPRP100	0	0	1	1	23.4 kg	38.0 cm	25.0 cm	25.0 cm



Multiple sales



Minimum sales



Box Width



Box Depth



Box Height