



WXETPRL

TUBULAR ROUND SLINGS

Fall protection



Specific benefits



Hygiene

- Harnesses and textiles can be washed with neutral soap

Applications

- Nafta in plin (pridobivanje)

Certifications and norms



WXETPRL

TUBULAR ROUND SLINGS

Fall protection

Standards - Details

Technical details

Type of equipment	Tubular round sling
Composition of the main support	Polyester
Max. length (m)	10 m
Strap width (mm)	75 mm
Min. length (m)	4 m
Color	Rdeča
SIZE	8 m
Type of packaging	Pack of 2
Suitable for	Low pressure
Pipe diameter- Maximum PSI	"2" - 15000 PSI, "3" - 8000 PSI, "4" - 5000 PSI








WXETPRL

TUBULAR ROUND SLINGS

Fall protection

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
WXETPRL0750400	Red	4 m	WXETPRL	7798408754757	0	2	1	10.4 kg	40.0 cm	30.0 cm	30.0 cm
WXETPRL0750600	Red	6 m	WXETPRL	0	0	2	1	15.4 kg	40.0 cm	30.0 cm	30.0 cm
WXETPRL0750800	Red	8 m	WXETPRL	7798408755310	0	1	1	10.15 kg	38.0 cm	25.0 cm	25.0 cm
WXETPRL0751000	Red	10 m	WXETPRL	0	0	1	1	12.6 kg	38.0 cm	25.0 cm	25.0 cm



Multiple sales



Minimum sales



Box Width



Box Depth



Box Height