



WXETPRL

ELINGUES RONDES TUBULAIRES

Fall protection



Specific benefits



Hygiene

- Can wash harnesses and textiles with neutral soap

Applications

- Oil & Gas (Extraction)

Certifications and norms



WXETPRL

ELINGUES RONDES TUBULAIRES

Fall protection

Standards - Details

Technical details

Type of equipment	Tubular round sling
Composition of the main support	Polyester
Max. length (m)	10 m
Strap width (mm)	75 mm
Min. length (m)	4 m
Color	Red
SIZE	8 m
Type of conditioning	Bag of 2
Suitable for	Low pressure
Pipe diameter- Maximum PSI	"2" - 15000 PSI, "3" - 8000 PSI, "4" - 5000 PSI








WXETPRL

TUBULAR ROUND SLINGS

Fall protection

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
WXETPRL0750400	Red	4 m	WXETPRL	7798408754757	0	2	1	10.4 kg	40.0 cm	30.0 cm	30.0 cm
WXETPRL0750600	Red	6 m	WXETPRL	0	0	2	1	15.4 kg	40.0 cm	30.0 cm	30.0 cm
WXETPRL0750800	Red	8 m	WXETPRL	7798408755310	0	1	1	10.15 kg	38.0 cm	25.0 cm	25.0 cm
WXETPRL0751000	Red	10 m	WXETPRL	0	0	1	1	12.6 kg	38.0 cm	25.0 cm	25.0 cm

 Multiple sales

 Minimum sales

 Box Width

 Box Depth

 Box Height