



ANSI527

ENERGY ABSORBING LANYARDS

Fall protection



Specific benefits



Hygiene

- Can wash harnesses and textiles with neutral soap



Performance

- Certification above maximum rated load 100kg; product certified at 140kg



Ease of Use

- Automatic carabiners for secure locking and time saving

Applications

- Building
- Maintenance
- Chemical Industry
- Petrochemical
- Storage

Certifications and norms

ANSI Z359.13-2013

Risk Protection



Fall



ANSI527

ENERGY ABSORBING LANYARDS

Fall protection

Standards - Details

Technical details

Type of equipment	Flat webbing lanyard
Composition of the main support	Steel, Polyester
Max. length (m)	1,8 m
Strap width (mm)	35 mm
Length (m)	1,8
Gate opening (mm)	65
Opening (inch)	2.5545
With connector	yes
Color	Black-Yellow
Lifespan from manufacturing (years)	10
Type of conditioning	box of 10
Fall arrest work situations	Vertical movement on a permanent structure, Movement on lifeline, Short vertical movement or movement on inclined surface (less than 3 m), Short horizontal movement (less than 3 m)
Lenght (ft)	5.9055



ANSI527

ENERGY ABSORBING LANYARDS

Fall protection

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
ANSI527	Black-Yellow	1,8 m	ANSI527	0	0	10	1	16.52 kg	38.0 cm	25.0 cm	25.0 cm

Multiple sales

Minimum sales

Box Width

Box Depth

Box Height