



LV511M

ROPE ACCESS WORK

Fall protection



Specific benefits



Hygiene

- Can wash harnesses and textiles with neutral soap

Applications

- Public Works
- Finishing Works/Craftsmanship
- Heavy Industry
- Light Industry
- Transportation

Certifications and norms



LV511M

ROPE ACCESS WORK

Fall protection

Standards - Details

Technical details

Composition of the main support	Steel, Polyamide
Max. length (m)	100 m
Min. length (m)	20 m
Color	White
SIZE	20 m
Connectors (structure side)	1 automatic lock hook, steel, opening 55mm
Lifespan from manufacturing (years)	10
Type of conditioning	Sold by Unit
Maximum number of users	1
Use	For ascent and descent, For vertical movement, For confined space
Fall arrest work situations	Work positioning, Rescue and evacuation, Long vertical movement or movement on inclined surface, Long vertical movement or movement on inclined surface for rope access work, Vertical movement, confined space
Opening (mm)	55 mm
Diameter (mm)	10,5








LV511M

ROPE ACCESS WORK

Fall protection

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
WXELV51120M	White	20 m	LV511M	7798408752746	0	1	1	2.2 kg	38.0 cm	25.0 cm	11.0 cm
WXELV51130M	White	30 m	LV511M	7798408752753	0	1	1	3.0 kg	38.0 cm	25.0 cm	11.0 cm
WXELV51140M	White	40 m	LV511M	7798408754191	0	1	1	4.0 kg	38.0 cm	25.0 cm	11.0 cm
WXELV51150M	White	50 m	LV511M	7798408754207	0	1	1	4.64 kg	38.0 cm	25.0 cm	17.0 cm
WXELV51160M	White	60 m	LV511M	7798408754214	0	1	1	5.57 kg	38.0 cm	25.0 cm	17.0 cm
WXELV511100M	White	100 m	LV511M	7798408754498	0	1	1	8.34 kg	38.0 cm	25.0 cm	25.0 cm



Multiple sales



Minimum sales



Box Width



Box Depth



Box Height