



E25120

2PLY SLINGS SF7

Fall protection



Specific benefits



Hygiene

· Harnesses and textiles can be washed with neutral soap

Applications

- Stavba
- Vzdrževanje
- Kemična industrija
- Petrokemija
- Shranjevanje

Certifications and norms



E25120

2PLY SLINGS SF7

Fall protection

Standards - Details

Technical details

Type of equipment	Flat sling
Composition of the main support	Polyester
Max. length (m)	8 m
Strap width (mm)	120 mm
Min. length (m)	2 m
Color	Siva
Safe working load (kg)	4000 kg
Type of split eye	Reduced








E25120

2PLY SLINGS SF7

Fall protection

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
WXE251200202	Grey	2 m	E25120	7798408752463	0	6	1	15.0 kg	40.0 cm	35.0 cm	28.0 cm
WXE251200302	Grey	3 m	E25120	7798408752470	0	6	1	19.0 kg	40.0 cm	30.0 cm	30.0 cm
WXE251200402	Grey	4 m	E25120	7798408753668	0	4	1	16.2 kg	40.0 cm	30.0 cm	30.0 cm
WXE251200502	Grey	5 m	E25120	7798408755525	0	4	1	19.2 kg	40.0 cm	30.0 cm	30.0 cm
WXE251200602	Grey	6 m	E25120	7798408753057	0	4	1	23.2 kg	40.0 cm	30.0 cm	30.0 cm
WXE251200702	Grey	7 m	E25120	0	0	2	1	14.0 kg	40.0 cm	30.0 cm	30.0 cm
WXE251200802	Grey	8 m	E25120	7798408753675	0	1	1	8.6 kg	40.0 cm	30.0 cm	30.0 cm



Multiple sales



Minimum sales



Box Width



Box Depth



Box Height