



E25030

2PLY SLINGS SF7

Fall protection



Specific benefits



Hygiene

· Harnesses and textiles can be washed with neutral soap

Applications

- Stavba
- Vzdrževanje
- Kemična industrija
- Petrokemija
- Shranjevanje

Certifications and norms



E25030

2PLY SLINGS SF7

Fall protection

Standards - Details

Technical details

Type of equipment	Flat sling
Composition of the main support	Polyester
Max. length (m)	8 m
Strap width (mm)	30 mm
Min. length (m)	1 m
Color	Violičná
Safe working load (kg)	1000 kg
Type of split eye	Flat








E25030

2PLY SLINGS SF7

Fall protection

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
WXE250300102	Purple	1 m	E25030	7798408750827	0	10	1	4.6 kg	38.0 cm	25.0 cm	11.0 cm
WXE250300202	Purple	2 m	E25030	7798408751893	0	8	1	6.0 kg	38.0 cm	25.0 cm	17.0 cm
WXE250300302	Purple	3 m	E25030	7798408752432	0	8	1	7.8 kg	38.0 cm	25.0 cm	17.0 cm
WXE250300402	Purple	4 m	E25030	7798408752449	0	8	1	9.6 kg	38.0 cm	25.0 cm	25.0 cm
WXE250300502	Purple	5 m	E25030	0	0	4	1	6.15 kg	38.0 cm	25.0 cm	17.0 cm
WXE250300602	Purple	6 m	E25030	7798408753613	0	6	1	10.4 kg	38.0 cm	25.0 cm	25.0 cm



Multiple sales



Minimum sales



Box Width



Box Depth



Box Height