



Fall protection

TC015

ROPE ACCESS WORK

Swinging double flange pulley, for rope work



Applications

- Building
- Finishing Works/Craftsmanship
- Maintenance
- Chemical Industry
- Petrochemical
- Power Energy

Certifications and norms



EN12278

30 KN

Risk Protection



Fall



Fall protection

TC015

ROPE ACCESS WORK

Swinging double flange pulley, for rope work

Standards - Details

Technical details

| | |
|-------------------------------------|---|
| Type of equipment | Double pulley with oscillating flanges |
| Composition of the main support | Aluminum |
| Color | Orange |
| SIZE | One size |
| Size | One size |
| Lifespan from manufacturing (years) | 20 |
| Weight (kg) | 0.430 |
| Use | Works on braided rope |
| Fall arrest work situations | Long vertical movement or movement on inclined surface for rope access work |








TC015

ROPE ACCESS WORK

Swinging double flange pulley, for rope work

Fall protection

Logistics information

| Reference | Colour | Size | Designation | EAN13 | Box code |  |  | Weight |  |  |  |
|-----------|--------|----------|-------------|---------------|----------------|---|---|--------|---|---|---|
| TC015 | Orange | One size | TC015 | 3295249186784 | 13295249186781 | 10 | 1 | 4.8 kg | 26.0 cm | 21.0 cm | 19.0 cm |

 Multiple sales

 Minimum sales

 Box Width

 Box Depth

 Box Height