



ANSILV5160

FALL ARRESTERS ON ROPE

Fall protection



Specific benefits



Hygiene

- Can wash harnesses and textiles with neutral soap



Performance

- Certification above maximum rated load 100kg; product certified at 140kg

Applications

- Building
- Oil & Gas (Extraction)
- Power Energy
- Storage

Certifications and norms



ANSILV5160

FALL ARRESTERS ON ROPE

Fall protection

Standards - Details

Technical details

Anchoring device	Lifeline
Composition of the main support	Polyamide
Max. length	100 m
Min. length	10 m
Rope diameter	16 mm
Color	White
SIZE	10 m
Lifespan from manufacturing	10 years
Diameter	16 mm








ANSILV5160

FALL ARRESTERS ON ROPE

Fall protection

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
ANSILV5160100	White	10 m	ANSILV5160	0	0	1	1	1.68 kg	38.0 cm	25.0 cm	11.0 cm
ANSILV5160200	White	20 m	ANSILV5160	0	0	1	1	3.12 kg	38.0 cm	25.0 cm	17.0 cm
ANSILV5160300	White	30 m	ANSILV5160	0	0	1	1	4.38 kg	38.0 cm	25.0 cm	17.0 cm
ANSILV5160400	White	40 m	ANSILV5160	0	0	1	1	5.8 kg	38.0 cm	25.0 cm	25.0 cm
ANSILV5160500	White	50 m	ANSILV5160	0	0	1	1	6.92 kg	40.0 cm	30.0 cm	30.0 cm
ANSILV5160800	White	80 m	ANSILV5160	0	0	1	1	11.0 kg	40.0 cm	35.0 cm	28.0 cm
ANSILV5161000	White	100 m	ANSILV5160	0	0	2	1	0.0 kg	0.0 cm	0.0 cm	0.0 cm

 Multiple sales

 Minimum sales

 Box Width

 Box Depth

 Box Height