



LVA50180

DISPOSITIFS D'ANCRAGE

Fall protection



Specific benefits



Hygiene

· Harnesses and textiles can be washed with neutral soap



Performance

· Certification above the maximum rated load of 100 kg; product certified at 140 kg

Applications

- Kemična industrija
- Nafta in plin (pridobivanje)
- Petrokemija
- Energija
- Shranjevanje

Certifications and norms



LVA50180

DISPOSITIFS D'ANCRAGE

Fall protection

Standards - Details

Technical details

Type of equipment	Extension strap in high tenacity polyester with D-ring.
Composition of the main support	Polyester
Max. length	1,8 m
Min. length	1,3 m
Length	1,8 m
Color	Črna-Rumena
SIZE	Enotna velikost
Type of packaging	Box of 10
Fall arrest work situations	Restraint, Rescue and evacuation, Long vertical movement or movement on inclined surface, Long vertical movement or movement on inclined surface for rope access work, Short vertical movement or movement on inclined surface (less than 3 m), Long horizontal movement on horizontal surface, Long horizontal movement on vertical structure, Short horizontal movement (less than 3 m)



LVA50180

ANCHORAGE DEVICES

Fall protection

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
WXELVA50180	Black-Yellow	One size	LVA50180	7798408754283	0	10	1	7.9 kg	38.0 cm	25.0 cm	17.0 cm

Multiple sales

Minimum sales

Box Width

Box Depth

Box Height