



LVA50180

ANCHORAGE DEVICES

Fall protection



Specific benefits



Hygiene

· Can wash harnesses and textiles with neutral soap



Performance

· Certification above maximum rated load 100kg; product certified at 140kg

Applications

- Chemical Industry
- Oil & Gas (Extraction)
- Petrochemical
- Power Energy
- Storage

Certifications and norms

ANSI Z359.18-2017



LVA50180

ANCHORAGE DEVICES

Fall protection

Standards - Details

Technical details

Type of equipment	Extension strap in high tenacity polyester with D-ring.
Composition of the main support	Polyester
Max. length	1,8 m
Min. length	1,3 m
Length	1,8 m
Color	Black-Yellow
SIZE	One size
Type of conditioning	box of 10
Fall arrest work situations	Restraint, Rescue and evacuation, Long vertical movement or movement on inclined surface, Long vertical movement or movement on inclined surface for rope access work, Short vertical movement or movement on inclined surface (less than 3 m), Long horizontal movement on horizontal surface, Long horizontal movement on vertical structure, Short horizontal movement (less than 3 m)



LVA50180

ANCHORAGE DEVICES

Fall protection

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
WXELVA50180	Black-Yellow	One size	LVA50180	7798408754283	0	10	1	7.9 kg	38.0 cm	25.0 cm	17.0 cm

Multiple sales

Minimum sales

Box Width

Box Depth

Box Height