



E26100

TUBULAR ROUND SLINGS

Fall protection



Specific benefits



Hygiene

· Harnesses and textiles can be washed with neutral soap

Applications

- Stavba
- Vzdrževanje
- Kemična industrija
- Petrokemija
- Shranjevanje

Certifications and norms



E26100

TUBULAR ROUND SLINGS

Fall protection

Standards - Details

Technical details

Type of equipment	Round sling
Composition of the main support	Polyester
Max. length (m)	8 m
Strap width (mm)	100 mm
Min. length (m)	2 m
Color	Oranžna
Safe working load (kg)	10000 kg








E26100

TUBULAR ROUND SLINGS

Fall protection

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
WXE261000210	Orange	2 m	E26100	0	0	1	1	5.154 kg	38.0 cm	25.0 cm	25.0 cm
WXE261000310	Orange	3 m	E26100	7798408755815	0	1	1	7.44 kg	38.0 cm	25.0 cm	25.0 cm
WXE261000610	Orange	6 m	E26100	7798408752586	0	1	1	14.297 kg	38.0 cm	25.0 cm	25.0 cm
WXE261000810	Orange	8 m	E26100	7798408753835	0	1	1	18.869 kg	38.0 cm	25.0 cm	25.0 cm
WXE261000910	Orange	9 m	E26100	0	0	1	1	21.154 kg	38.0 cm	25.0 cm	25.0 cm
WXE261001010	Orange	10 m	E26100	0	0	1	1	23.44 kg	38.0 cm	25.0 cm	25.0 cm

 Multiple sales

 Minimum sales

 Box Width

 Box Depth

 Box Height