



E26075

TUBULAR ROUND SLINGS

Fall protection



Specific benefits



Hygiene

· Harnesses and textiles can be washed with neutral soap

Applications

- Stavba
- Vzdrževanje
- Kemična industrija
- Petrokemija
- Shranjevanje

Certifications and norms



E26075

TUBULAR ROUND SLINGS

Fall protection

Standards - Details

Technical details

Type of equipment	Round sling
Composition of the main support	Polyester
Max. length (m)	8 m
Strap width (mm)	75 mm
Min. length (m)	1 m
Color	Rdeča
Safe working load (kg)	5000 kg








E26075

TUBULAR ROUND SLINGS

Fall protection

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
WXE260750205	Red	2 m	E26075	7798408752524	0	4	1	10.468 kg	38.0 cm	25.0 cm	25.0 cm
WXE260750305	Red	3 m	E26075	7798408753118	0	2	1	7.814 kg	38.0 cm	25.0 cm	17.0 cm
WXE260750405	Red	4 m	E26075	7798408752531	0	2	1	10.402 kg	38.0 cm	25.0 cm	25.0 cm
WXE260750505	Red	5 m	E26075	7798408752548	0	2	1	12.852 kg	38.0 cm	25.0 cm	25.0 cm
WXE260750605	Red	6 m	E26075	7798408752173	0	2	1	15.362 kg	40.0 cm	30.0 cm	30.0 cm
WXE260750905	Red	9 m	E26075	0	0	1	1	11.354 kg	38.0 cm	25.0 cm	25.0 cm
WXE260751005	Red	10 m	E26075	0	0	1	1	12.579 kg	38.0 cm	25.0 cm	25.0 cm

 Multiple sales

 Minimum sales

 Box Width

 Box Depth

 Box Height