



ANSI559RD

LONGES ABSORBEUR D'ÉNERGIE

Fall protection



Specific benefits



Comfort

- Elastic strap lanyard for easy movement and safety



Hygiene

- Harnesses and textiles can be washed with neutral soap



Performance

- Certification above the maximum rated load of 100 kg; product certified at 140 kg



Easy to use

- Automatic carabiners for secure and time-saving locking
- NFC system guarantees traceability

Applications

- Stavba
- Kemična industrija
- Nafta in plin (pridobivanje)
- Petrokemija
- Shranjevanje

Certifications and norms

Protects against risks



Heat



Fall



Electrical



ANSI559RD

LONGES ABSORBEUR D'ÉNERGIE

Fall protection

Standards - Details

Technical details

Composition of the main support	Kevlar®, Steel, Plastic
Max. length (m)	1,8 m
Gate opening (mm)	65
Opening (inch)	2.5545
With connector	yes
Color	Rdeča
SIZE	Enotna velikost
Benefits element	Elastic strap, Dielectric
Lifespan from manufacturing (let)	10
Type of packaging	Box of 10
Fall arrest work situations	Vertical movement on a permanent structure, Movement on lifeline, Short vertical movement or movement on inclined surface (less than 3 m), Short horizontal movement (less than 3 m)



ANSI559RD

ENERGY ABSORBING LANYARDS

Fall protection

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
ANSI559RD	Red	1,8 m	ANSI559RD	0	0	10	1	16.2 kg	38.0 cm	25.0 cm	25.0 cm

Multiple sales

Minimum sales

Box Width

Box Depth

Box Height