



# ANSI559RD

## ENERGY ABSORBING LANYARDS

Fall protection



### Specific benefits



#### Comfort

- Elastic webbing lanyard for easy movement and safety



#### Hygiene

- Can wash harnesses and textiles with neutral soap



#### Performance

- Certification above maximum rated load 100kg: product certified at 140kg



#### Ease of Use

- Automatic carabiners for secure locking and time saving
- NFC system guarantees traceability

### Applications

- Building
- Chemical Industry
- Oil & Gas (Extraction)
- Petrochemical
- Storage

### Certifications and norms

ANSI Z359.13-2013

### Risk Protection



Heat



Fall



Electrical



# ANSI559RD

## ENERGY ABSORBING LANYARDS

Fall protection

### Standards - Details

### Technical details

Composition of the main support	Kevlar®, Steel, Plastic
Max. length (m)	1,8 m
Gate opening (mm)	65
Opening (inch)	2.5545
With connector	yes
Color	Red
SIZE	One size
Benefits element	Elastic strap, Dielectric
Lifespan from manufacturing (years)	10
Type of conditioning	box of 10
Fall arrest work situations	Vertical movement on a permanent structure, Movement on lifeline, Short vertical movement or movement on inclined surface (less than 3 m), Short horizontal movement (less than 3 m)



# ANSI559RD

## ENERGY ABSORBING LANYARDS

Fall protection

### Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
ANSI559RD	Red	1,8 m	ANSI559RD	0	0	10	1	16.2 kg	38.0 cm	25.0 cm	25.0 cm

Multiple sales

Minimum sales

Box Width

Box Depth

Box Height