



E26060

TUBULAR ROUND SLINGS

Fall protection



Specific benefits



Hygiene

· Harnesses and textiles can be washed with neutral soap

Applications

- Stavba
- Vzdrževanje
- Kemična industrija
- Petrokemija
- Shranjevanje

Certifications and norms



E26060

TUBULAR ROUND SLINGS

Fall protection

Standards - Details

Technical details

Type of equipment	Round sling
Composition of the main support	Polyester
Max. length (m)	8 m
Strap width (mm)	75 mm
Min. length (m)	1 m
Color	Rumena
Safe working load (kg)	3000 kg








E26060

TUBULAR ROUND SLINGS

Fall protection

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
WXE260600103	Yellow	1 m	E26060	7798408751947	0	2	1	2.116 kg	38.0 cm	25.0 cm	17.0 cm
WXE260600203	Yellow	2 m	E26060	7798408751022	0	2	1	3.604 kg	38.0 cm	25.0 cm	11.0 cm
WXE260600303	Yellow	3 m	E26060	7798408751954	0	2	1	5.254 kg	38.0 cm	25.0 cm	17.0 cm
WXE260600403	Yellow	4 m	E26060	7798408752159	0	2	1	7.062 kg	38.0 cm	25.0 cm	17.0 cm
WXE260600503	Yellow	5 m	E26060	7798408753750	0	2	1	8.912 kg	40.0 cm	30.0 cm	30.0 cm
WXE260600603	Yellow	6 m	E26060	0	0	2	1	10.362 kg	38.0 cm	25.0 cm	17.0 cm
WXE260600703	Yellow	7 m	E26060	0	0	2	1	12.21 kg	40.0 cm	30.0 cm	30.0 cm
WXE260600803	Yellow	8 m	E26060	7798408753767	0	2	1	13.86 kg	40.0 cm	30.0 cm	30.0 cm
WXE260600903	Yellow	9 m	E26060	0	0	2	1	15.508 kg	40.0 cm	30.0 cm	30.0 cm
WXE260601003	Yellow	10 m	E26060	0	0	2	1	17.158 kg	40.0 cm	30.0 cm	30.0 cm

 Multiple sales

 Minimum sales

 Box Width

 Box Depth

 Box Height