



CV1026XLM65

LONGES ABSORBEUR D'ÉNERGIE

Fall protection



Specific benefits



Hygiene

- Harnesses and textiles can be washed with neutral soap



Performance

- Certification above the maximum rated load of 100 kg; product certified at 140 kg



Easy to use

- Automatic carabiners for secure and time-saving locking



Compatibility

- Compatible with all kind of harnesses

Applications

- Stavba
- Lahka industrija
- Petrokemija
- Energija
- Shranjevanje

Certifications and norms



CV1026XLM65

LONGES ABSORBEUR D'ÉNERGIE

Fall protection

Standards - Details

Technical details

Type of equipment	Flat webbing lanyard
Composition of the main support	Steel, Polyester
Max. length (m)	1,5 m
Strap width (mm)	45 mm
With connector	yes
Color	Črna-Oranžna
Connector (user side)	Automatic lock hook, steel, opening 18mm
SIZE	1.50 m
Connector (structure side)	2 self-locking hooks, steel, opening 60 mm
Lifespan from manufacturing (let)	10
Type of packaging	Box of 5
Fall arrest work situations	Vertical movement on a permanent structure, Movement on lifeline, Short vertical movement or movement on inclined surface (less than 3 m), Short horizontal movement (less than 3 m), Long movement with multi connection /disconnection








CV1026XLM65

ENERGY ABSORBING LANYARDS

Fall protection

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
WXECV1026XLM65	Black-Orange	1.50 m	CV1026XLM65	7798408753163	0	2	1	3.48 kg	38.0 cm	25.0 cm	11.0 cm



Multiple sales



Minimum sales



Box Width



Box Depth



Box Height