



E25150

ELINGUES 7:1 IN DOUBLE PLI

Fall protection



Specific benefits



Hygiene

- Can wash harnesses and textiles with neutral soap

Applications

- Building
- Maintenance
- Chemical Industry
- Petrochemical
- Storage

Certifications and norms



E25150

ELINGUES 7:1 IN DOUBLE PLI

Fall protection

Standards - Details

Technical details

Type of equipment	Flat sling
Composition of the main support	Polyester
Max. length (m)	8 m
Strap width (mm)	150 mm
Min. length (m)	2 m
Safe working load (kg)	5000 kg
Type of split eye	Reduced








E25150

2PLY SLINGS SF7

Fall protection

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
WXE251500202	Red	2 m	E25150	7798408753682	0	4	1	7.7 kg	40.0 cm	30.0 cm	30.0 cm
WXE251500302	Red	3 m	E25150	7798408752135	0	4	1	16.6 kg	40.0 cm	30.0 cm	30.0 cm
WXE251500402	Red	4 m	E25150	0	0	4	1	22.4 kg	40.0 cm	30.0 cm	30.0 cm
WXE251500502	Red	5 m	E25150	7798408751916	0	2	1	16.4 kg	40.0 cm	30.0 cm	30.0 cm
WXE251500602	Red	6 m	E25150	7798408753064	0	2	1	20.0 kg	40.0 cm	30.0 cm	30.0 cm
WXE251500702	Red	7 m	E25150	0	0	1	1	12.0 kg	38.0 cm	25.0 cm	25.0 cm



Multiple sales



Minimum sales



Box Width



Box Depth



Box Height