



E25090

2PLY SLINGS SF7

Fall protection



Specific benefits



Hygiene

· Harnesses and textiles can be washed with neutral soap

Applications

- Stavba
- Vzdrževanje
- Kemična industrija
- Petrokemija
- Shranjevanje

Certifications and norms



E25090

2PLY SLINGS SF7

Fall protection

Standards - Details

Technical details

Type of equipment	Flat sling
Composition of the main support	Polyester
Max. length (m)	8 m
Strap width (mm)	90 mm
Min. length (m)	1 m
Safe working load (kg)	3000 kg
Type of split eye	Reduced








E25090

2PLY SLINGS SF7

Fall protection

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
WXE250900102	Yellow	1 m	E25090	7798408753033	0	6	1	6.96 kg	38.0 cm	25.0 cm	25.0 cm
WXE250900202	Yellow	2 m	E25090	7798408753644	0	8	1	14.6 kg	40.0 cm	30.0 cm	30.0 cm
WXE250900302	Yellow	3 m	E25090	7798408751909	0	8	1	7.06 kg	50.0 cm	40.0 cm	33.0 cm
WXE250900402	Yellow	4 m	E25090	7798408752456	0	4	1	13.22 kg	40.0 cm	30.0 cm	30.0 cm
WXE250900502	Yellow	5 m	E25090	7798408753040	0	4	1	16.0 kg	40.0 cm	30.0 cm	30.0 cm
WXE250900602	Yellow	6 m	E25090	7798408752128	0	4	1	18.5 kg	40.0 cm	30.0 cm	30.0 cm
WXE250900802	Yellow	8 m	E25090	7798408753651	0	2	1	12.35 kg	40.0 cm	30.0 cm	30.0 cm



Multiple sales



Minimum sales



Box Width



Box Depth



Box Height