



# E25060

## 2PLY SLINGS SF7

Fall protection



### Specific benefits



#### Hygiene

· Harnesses and textiles can be washed with neutral soap

### Applications

- Stavba
- Vzdrževanje
- Kemična industrija
- Petrokemija
- Shranjevanje

### Certifications and norms



# E25060

## 2PLY SLINGS SF7

Fall protection

### Standards - Details

### Technical details

Type of equipment	Flat sling
Composition of the main support	Polyester
Max. length (m)	8 m
Strap width (mm)	60 mm
Min. length (m)	1 m
Safe working load (kg)	2000 kg
Type of split eye	Flat








# E25060

## 2PLY SLINGS SF7

Fall protection

### Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
WXE250600102	Green	1 m	E25060	7798408752104	0	8	1	5.8 kg	38.0 cm	25.0 cm	17.0 cm
WXE250600202	Green	2 m	E25060	7798408752111	0	6	1	6.6 kg	38.0 cm	25.0 cm	17.0 cm
WXE250600302	Green	3 m	E25060	7798408751305	0	8	1	12.2 kg	38.0 cm	25.0 cm	25.0 cm
WXE250600402	Green	4 m	E25060	7798408753620	0	8	1	15.2 kg	38.0 cm	25.0 cm	25.0 cm
WXE250600502	Green	5 m	E25060	7798408751503	0	4	1	10.42 kg	38.0 cm	25.0 cm	17.0 cm
WXE250600802	Green	8 m	E25060	7798408753637	0	2	1	8.0 kg	38.0 cm	25.0 cm	17.0 cm



Multiple sales



Minimum sales



Box Width



Box Depth



Box Height