



# ANSI560 Yellow

## ENERGY ABSORBING LANYARDS

Fall protection



### Specific benefits



#### Comfort

- Elastic webbing lanyard for easy movement and safety



#### Hygiene

- Can wash harnesses and textiles with neutral soap



#### Performance

- Certification above maximum rated load 100kg: product certified at 140kg



#### Ease of Use

- Automatic carabiners for secure locking and time saving



#### Compatibility

·

### Applications

- Building
- Maintenance
- Chemical Industry
- Petrochemical
- Storage

### Certifications and norms

ANSI Z359.13-2013

### Risk Protection



Heat



Fall



# ANSI560 Yellow

## ENERGY ABSORBING LANYARDS

Fall protection

### Standards - Details

### Technical details

Composition of the main support	Kevlar®, Steel
Max. length (m)	1,8 m
Length (m)	1,8
Gate opening (mm)	65
Opening (inch)	2.5545
With connector	yes
Color	Yellow
Benefits element	Elastic strap
Lifespan from manufacturing (years)	10
Type of conditioning	Box of 5
Fall arrest work situations	Vertical movement on a permanent structure, Movement on lifeline, Short vertical movement or movement on inclined surface (less than 3 m), Short horizontal movement (less than 3 m), Long movement with multi connection /disconnection
Lenght (ft)	5.9055



# ANSI560

## ENERGY ABSORBING LANYARDS

Fall protection

### Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
ANSI560	Red	1,8 m	ANSI560	7798408752876	0	5	1	12.8 kg	38.0 cm	25.0 cm	25.0 cm

 Multiple sales

 Minimum sales

 Box Width

 Box Depth

 Box Height