



ANSI559

LONGES ABSORBEUR D'ÉNERGIE

Fall protection



Specific benefits



Comfort

- Elastic strap lanyard for easy movement and safety



Hygiene

- Harnesses and textiles can be washed with neutral soap



Performance

- Certification above the maximum rated load of 100 kg; product certified at 140 kg



Easy to use

- Automatic carabiners for secure and time-saving locking

Certifications and norms

Applications

- Stavba
- Vzdrževanje
- Kemična industrija
- Petrokemija
- Shranjevanje

Protects against risks



Heat



Fall



ANSI559

LONGES ABSORBEUR D'ÉNERGIE

Fall protection

Standards - Details

Technical details

| | |
|-----------------------------------|--|
| Composition of the main support | Kevlar®, Steel |
| Max. length (m) | 1,8 m |
| Length (m) | 1,8 |
| Gate opening (mm) | 65 |
| Opening (inch) | 2.5545 |
| With connector | yes |
| Benefits element | Elastic strap |
| Lifespan from manufacturing (let) | 10 |
| Type of packaging | Box of 10 |
| Fall arrest work situations | Vertical movement on a permanent structure, Movement on lifeline, Short vertical movement or movement on inclined surface (less than 3 m), Short horizontal movement (less than 3 m) |
| Lenght (ft) | 5.9055 |








ANSI559

ENERGY ABSORBING LANYARDS

Fall protection

Logistics information

| Reference | Colour | Size | Designation | EAN13 | Box code |  |  | Weight |  |  |  |
|-----------|--------|-------|-------------|-------|----------|---|---|---------|---|---|---|
| ANSI559 | Red | 1,8 m | ANSI559 | 0 | 0 | 10 | 1 | 16.2 kg | 38.0 cm | 25.0 cm | 25.0 cm |

 Multiple sales

 Minimum sales

 Box Width

 Box Depth

 Box Height